




# HANDSET BOARD



# CRT BOARD



# WAVEFORM



# REMARK :

- 5.5MHz FOR CF
- 6.0MHz FOR CF2

# NOTE:

- (1) ALL CAPACITORS ARE IN uF UNLESS OTHERWISE NOTED.
- (2) CAPACITOR NOT SPECIFICALLY DESIGNATED ARE CERAMIC CAPACITORS.
- (3) ALL RESISTORS ARE IN OHM 1/16 WATT UNLESS OTHERWISE NOTED.
- (4) RESISTOR NOT SPECIFICALLY DESIGNATED ARE CARBON FILM RESISTORS.
- (5) DC VOLTAGE ARE MEASURED FROM POINTS INDICATED TO THE CIRCUIT GROUND WITH A DIGITAL MULTIMETER TEST.
- (6) WAVEFORMS ARE TAKEN WITH SETTING CONTROLS TO A NORMAL CONDITIONS ( COLOR PHILIPS PATIEN ).
- (7) THIS CIRCUIT DIAGRAM IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.
- (8) SAFETY CRITICAL DEVICE.

# CIRCUIT SYMBOLS

RESISTOR			CAPACITOR	
	NONFLAMMBLE			ELECTROLYC
	FUSEBLE			POLYPROPYLENE
	CEMENT			MYLAR
	METAL OXIDE			TANTALUM
	THERMISTOR			BI-POLAR ELECTROLYC
				METALLIZED POLYESTER
				POLYESTER FILM

MODEL : CT-3012PT(10K40)	SYSTEM: PAL B/G
DRAWING NO. : 9220-08	PAGE 1 OF 1
DRAWN BY:	APPROVED:
DATE: FEB 12. 83	(PROJECT LEADER)
	REV NO. : B(04-05-85)

# SCHEMATIC DIAGRAM FOR PAL B/G SYSTEM

RECEIVE BOARD

MAIN BOARD

